

SP-FSC842D/872D series

双针电脑平缝机
Double-Needle Computerized
Lockstitch Machine



电脑直驱款 SP-FSC842D/872D 标配自动剪线、自动倒回缝、自动扫线功能；
Computer direct drive model SP-FSC842D/872D Standard-equipped with Automatic Thread Trimming, Automatic Reverse Stitching, and Automatic fastening stitching Functions.

性能优势:

电脑双针缝纫机采用计算机控制系统、交流伺服电机直驱,具有自动调速、停针位、剪线、计针数、倒顺缝、加固缝等功能。

1. 驱动轴采用 850W 交流伺服电机直驱形式；
2. 针杆和挑线杆采用微油或油脂润滑；
3. 具有自动剪线功能、自动扫线功能、自动倒缝功能；
4. 机头内部上下轴传动采用同步带机构形式；

适用范围:

适用于衬衣、休闲装、茄克衬、牛仔装、羽绒服等,风衣的下摆、棉衣的袋盖、帐篷及汽车内饰等需要双锁式线迹缝纫。


Advantages

The computer double-needle machine shall adopt computer control system, AC servo motor direct drive, and have the functions of automatic speed regulation, needle stop position, thread trimming, stitching counting, reverse sewing, reinforcement sewing, etc.


1. The drive shaft adopts the form of 850W AC servo motor direct drive.
2. Needle rod and take-up rod are lubricated with less oil or grease.
3. With automatic thread trimming function, automatic thread sweeping function, automatic reverse sewing function;
4. The transmission of the upper and lower shafts inside the machine head adopts the synchronous belt mechanism;

Application

It is suitable for shirts, casual wear, jacket lining, denim, down jacket, etc. The hem of windbreaker, pocket flap of cotton coat, tent and car interior, etc.



通过调节挑线杆的线量,对应从薄料到中厚料的缝制。通过最佳的设定,可以对应各种面料。
By adjusting the thread tension of the thread take-up lever, you can achieve stitching results that correspond to various fabric thicknesses, from thin to medium-weight fabrics. By finding the optimal settings, the sewing machine can adapt to different fabric types effectively.



双直刀剪线机构反应速度快,在更换针位时方便剪线调整,使用粗线时效果特别明显。
The direct knife thread trimming mechanism offers a fast response speed, making it convenient for adjusting thread trimming when changing needle positions. It is particularly effective when working with thicker threads.



通过在操作盘上简单的数字设定,可以调整缝纫速度、设定上下停针位,计算已缝制的针数作为生产计数器使用等各项功能。
You can select different decorative stitch patterns according to the sewing process requirements. Additionally, you have the option to customize and create your own desired stitch patterns. This allows you to sew with stylish and aesthetically pleasing stitch lines, adding an attractive element to your sewing projects.



小油盒密封,避免粉尘线毛进入机腔内,清洁耐久,便捷搬移,不撒油;
The small oil reservoir is sealed to prevent the entry of dust, lint, or debris into the machine chamber. This design ensures cleanliness and durability, making it convenient for transportation without any oil spills.

型号 Model	-403/-405	压脚上升量 Lifting height of prsser foot	7mm
用途 Application	中厚料 / 厚料	马达 Motor	AC 伺服马达 850W
最高缝制速度 Maximum sewing speed	3200rpm/3000rpm/	电源 Power supply	单相 220V
机针 Machine needle	DPx5 #14/DPx5 #22	净重 / 毛重 Net/gross weight(Kg)	52/62
最大针距 Maximum stitch length	4mm/5mm	包装尺寸 Package size	720×310×670mm